



Cisco Packet Tracer Pod Installation and Configuration Guide

Document Version: **2020-11-17**

Copyright © 2020 Network Development Group, Inc.
www.netdevgroup.com

NETLAB+ is a registered trademark of Network Development Group, Inc.

Microsoft® and Windows® are registered trademarks of Microsoft Corporation in the United States and other countries.

VMware is a registered trademark of VMware, Inc.

Cisco, IOS, Cisco IOS, Networking Academy, CCNA, and CCNP are registered trademarks of Cisco Systems, Inc.

Contents


1	Introduction	3
1.1	Introducing the Cisco Packet Tracer Pod.....	3
2	Planning.....	4
2.1	Pod Creation Workflow	4
2.2	Pod Resource Requirements	5
2.3	ESXi Host Server Requirements	5
2.4	NETLAB+ Requirements.....	5
2.5	NETLAB+ Virtual Machine Infrastructure Setup	6
2.6	Software Requirements.....	6
2.7	Networking Requirements.....	6
2.7.1	Pod Internet Access.....	7
2.7.2	Completing the NETLAB+ Pod Internet Access and Use Agreement.....	7
3	Software and Licenses	8
3.1	Downloading OVF Files.....	8
4	Master Pod Configuration.....	9
4.1	Deploying Virtual Machine OVF/OVA Files.....	9
4.1.1	Modify Virtual Machines	10
4.2	NETLAB+ Virtual Machine Inventory Setup	13
4.3	Building the Master Pod	15
4.3.1	Enabling Lab Content in Course Manager	15
4.3.2	Create the Master Pod	15
4.3.3	Attach Virtual Machines to the Master Pod	16
4.3.4	Create Snapshots for the Master Virtual Machines.....	17
4.3.5	Set the Revert to Snapshot	20
4.3.6	Bring the Master Pod Online	21
4.4	Testing the Master Pod (optional)	21
4.4.1	Virtual Machine Credentials	21
4.4.2	Create Class and Schedule the Master Pod.....	21
4.4.3	Test the Master Pod	22
4.4.4	End Reservation	22
4.4.5	Take the Master Pod Offline.....	22
5	Pod Cloning	23
5.1	Linked Clones and Full Clones.....	23
5.2	Creating User Pods	23
5.3	Copying Your Master Pod to the Second Host	26
5.4	Creating User Pods on the Second Host.....	27
5.5	Assigning Pods to Students, Teams, or Classes	27

1 Introduction

This document provides detailed guidance on performing the installation and configuration of the Cisco Packet Tracer Pod on the *NETLAB+ VE* system.

1.1 Introducing the Cisco Packet Tracer Pod

The *Cisco Packet Tracer Pod* is a 100% virtual machine pod consisting of two virtual machines.



2 Planning

This guide provides specific information pertinent to delivering the *Cisco Packet Tracer Pod*. The [NETLAB+ Remote PC Guide Series](#) provides the prerequisite guidance for setting up your VMware infrastructure, including:

- An introduction to virtualization using *NETLAB+*
- Detailed setup instructions for standing up *VMware vCenter* and *VMware ESXi*
- Virtual machine and virtual pod management concepts using *NETLAB+*

This document assumes that you have set up virtual machine infrastructure in accordance with the [NETLAB+ Remote PC Guide Series](#). The planning information below refers to specific sections in the *Remote PC Guide* when applicable.

2.1 Pod Creation Workflow

The following list is an overview of the pod setup process.

1. Obtain the master virtual machine images required for the master pod.
2. Deploy the master virtual machine images to your *VMware vCenter Appliance*.
 - a. Deploy virtual machines using **Thin Provisioning** to reduce storage consumption.
 - b. Make necessary adjustments to each virtual machine in the environment.
 - i. Insert/Verify manual **MAC** addresses.
 - ii. Change the default network to **SAFETY NET**.
 - iii. Any other configuration changes mentioned in this guide.
3. Import the deployed virtual machines to the *NETLAB+ Virtual Machine Inventory*.
4. Activate or license the required software on each virtual machine when prompted.
5. Take a snapshot of each virtual machine in the master pod labeled **GOLDEN_MASTER** after all configurations and licensing have taken effect. The *GOLDEN_MASTER* snapshot is used to clone virtual machine images for the user pods.
6. Use the *NETLAB+ Pod Cloning* feature to create student pods from the master pod.
7. If multiple hosts are used in the *NETLAB+* environment, make a **Full Clone** of the master pod on the initial host (Host A) to the subsequent host (Host B) and so on using the *NETLAB+ Pod Cloning* feature.

2.2 Pod Resource Requirements

The *Cisco Packet Tracer Pod* will consume 10 GB of storage per each master pod instance.

The following table provides details of the storage requirements for each of the virtual machines in the pod.

Virtual Machine	OVF/OVA	Initial Master Pod (Thin Provisioned)
Workbench	4.3 GB	9.8 GB
Pod Router	62 MB	180 MB
Total	4.4 GB	10 GB

2.3 ESXi Host Server Requirements

Please refer to the *NDG* website for specific *ESXi* host requirements to support virtual machine delivery: <https://www.netdevgroup.com/products/requirements/>

The deployment of the *Cisco Packet Tracer Pod* requires VMware ESXi version of **6.0** or greater.

Please Note

The number of **active** pods that can be used simultaneously depends on the *NETLAB+* product license and the number of *VMware ESXi* host servers meeting the hardware requirements specifications.

2.4 NETLAB+ Requirements

Installation of *Cisco Packet Tracer Pod*, as described in this guide, requires that you are running *NETLAB+ VE*.

Previous versions of *NETLAB+* do not support requirements for the *Cisco Packet Tracer Pod* on the physical host servers.

Please refer to the [NETLAB+ Remote PC Guide Series](#).

2.5 NETLAB+ Virtual Machine Infrastructure Setup

The *NETLAB+ Virtual Machine Infrastructure* setup is described in the following sections of the [NETLAB+ Remote PC Guide Series](#):

- *Registering a Virtual Datacenter in NETLAB+*
- *Adding ESXi hosts in NETLAB+*
- *Proactive Resource Awareness*



It is important to configure *Proactive Resource Awareness* to maximize the number of active pods per physical *ESXi* host.

2.6 Software Requirements

For the purpose of software licensing, each virtual machine is treated as an individual machine, PC, or server. Please refer to the specific vendor license agreements (and educational discount programs, if applicable) to determine licensing requirements for your virtual machines' software, operating system, and applications.

The minimum virtual infrastructure software required for standing up this pod is in the following table.

Virtual Infrastructure Requirements	
Software	Version
vSphere ESXi	6.0
vCenter Server	6.0

Please refer to the *Software and Licenses* section regarding the software requirements for virtual machines in the pod.

2.7 Networking Requirements

To accommodate the movement of large *VMs*, *OVF/OVAs*, and *ISO* disk images from one host to another, gigabit Ethernet or better connectivity is recommended to interconnect your *NETLAB+*, *vCenter Server* system, and *ESXi* host systems.

The two standard networking models recommended to interconnect your servers are described in detail in the *Networking Models* section of the [Remote PC Guide Series, Volume 1 - Introduction and Planning](#).

2.7.1 Pod Internet Access

The *Cisco Packet Tracer Pod* requires internet access. This access is required to access the Cisco Network Academy curriculum as well as completing the lab objectives in the student pods.

This environment is designed to leverage one vSwitch per host that attaches to a network that has a DHCP server to assign IPv4 addresses that are routable to the internet.

This lab environment is also designed to leverage the public DNS servers 8.8.8.8 and 4.2.2.2. This vSwitch must be able to access those servers, which may require adjustments in a firewall if applicable.

2.7.2 Completing the NETLAB+ Pod Internet Access and Use Agreement



You are required to complete the *NETLAB+ Pod Internet Access and Use Agreement* prior to obtaining access to the pod or content for this course.

Due to the security and legal implications regarding accessing the internet from within the pod, we require that you agree to the terms contained within this online document prior to obtaining access to the pod or content for this course:

<https://www.netdevgroup.com/content/cnap/ptagreement>

3 Software and Licenses

3.1 Downloading OVF Files

The virtual machines are made available as *Open Virtualization Format (OVF)* or *Open Virtualization Archive (OVA)* files. These files are available for download from *CSSIA*.

To request access to the preconfigured virtual machine templates from *CSSIA*:

1. Go to the *CSSIA Resources* page: <https://www.cssia.org/cssiaresources/>
2. Select **CSSIA VM Image Sharing Agreement**.
3. Complete and submit your access request by following the instructions on the request form.
4. *CSSIA* will provide, via email, password-protected download links. Access to the download links is provided only to customers who are current with their NETLAB+ support contract and are participants in the appropriate partner programs (*i.e.*, *Cisco Networking Academy*, *VMware IT Academy*, *Red Hat Academy*, and/or *Palo Alto Networks*).
5. Once all virtual machines have been downloaded, they can be deployed following the steps in the appropriate pod installation guide. Each virtual machine is deployed individually.

4 Master Pod Configuration

4.1 Deploying Virtual Machine OVF/OVA Files

Deploy on your host server the pod virtual machine *OVF/OVA* files you have downloaded.

1. Navigate to your **vSphere Client** using your management workstation, ensure that your downloaded *OVA/OVF* files are accessible on this machine, and then connect to your **vCenter Server**.
2. From the *vSphere Client* interface, navigate to **Hosts and Clusters**.
3. Right-click on the target **ESXi Host Server** and select **Deploy OVF Template**.
4. In the *Deploy OVF Template* window, on the *Select source* step, select the **Local File** radio button and click **Browse**.
5. Locate and select one of the VMs for the pod, click **Open**.

Virtual Machine	VM OS	Virtual Machine File Name
Pod Router	Linux	CiscoPT73.PodRouter.ova
Workbench	Linux	CiscoPT73.Workbench.ova

6. Verify that the VM information populates next to the *Browse* button and click **Next**.

Please Note

Only one VM can be selected using this wizard. The process will have to be repeated for the remaining VMs.

7. On the *Review details* step, make sure to click the checkbox for **Accept extra configuration options** (*if present*) and click **Next**.
8. On the *Select name and folder* step, change the name of the virtual machine to something that is easy to manage. You can use the names provided in the list below as names for the virtual machines if you do not have a set naming convention. Select the appropriate **datacenter** and click **Next**.

Virtual Machine	VM OS	Virtual Machine Deployment Name
Pod Router	Linux	Cisco_Packet_Tracer_Master.PodRouter
Workbench	Linux	Cisco_Packet_Tracer_Master.Workbench

9. On the *Select Storage* step, choose the appropriate storage device and make sure that **Thin Provision** is selected. Click **Next**.

10. In the *Setup networks* section, select **SAFETY NET** as the destination and click **Next**.



If *SAFETY NET* is not available, refer to the *Create a Safe Staging Network* section in the [Remote PC Guide Series – Volume 2](#).

11. In the *Ready to complete* section, make sure **Power on after deployment** is **unchecked** and confirm the settings. Click **Finish**.
12. *vCenter* will begin deploying the virtual machine. This may take some time depending on the speed of your connection, HDDs, etc.


4.1.1 Modify Virtual Machines

Once the virtual machines are imported onto the host, verify the configurations. The following steps will guide you through the process.


1. In the *vSphere Client* interface, right-click on the imported virtual machine and select **Edit Settings**.
2. For all the virtual machines, manually assign the *MAC* addresses for each *NIC*. The table below identifies the *MAC* addresses per *NIC*.

Virtual Machine	NIC	Network	MAC
Pod Router	1	Network with DHCP Internet Access	Automatic
	2	Safety_Net	00:50:56:99:2d:2f
Client	1	Safety_Net	00:50:56:99:d0:99

- For the *Pod Router* virtual machine, change *Network adapter 1* to the network that has DHCP Internet access available as well as making sure that the MAC is set to **Automatic**, see [Pod Internet Access](#) and change *Network adapter 2* to the **Safety_Net** network as well as making sure the MAC address is set to **Manual** and changed to **00:50:56:99:2d:2f**.



4. For the *Workbench* virtual machine, change *Network adapter 2* to the **Safety_Net** network as well as making sure the MAC address is set to **Manual** and changed to **00:50:56:99:d0:99**.



4.2 NETLAB+ Virtual Machine Inventory Setup

This section will guide you in adding your templates to the *Virtual Machine Inventory* of your *NETLAB+ VE* system.

1. Log in to your *NETLAB+ VE* system using the administrator account.
2. Select the **Virtual Machine Infrastructure** icon.




3. Click the **Virtual Machine Inventory** icon.




Virtual Machine Inventory

Import, clone, and manage the inventory of virtual machines to be used with NETLAB+.

4. Click the **Import Virtual Machines** button located at the bottom of the list.



5. Select the appropriate datacenter from the list where your master VMs reside.
6. Select the checkbox next to the virtual machines you had just deployed and click **Import Selected Virtual Machines**.




7. When the *Configure VMs* window loads, you can set your virtual machine parameters.
 - a. Check the dropdown box for the correct operating system for each imported virtual machine.
 - b. Change *Role* to **Master** for each VM.
 - c. Add any comments for each virtual machine in the last column.



It is advised to leave the *Version* and *Build* numbers for reference when requesting *NDG* support.

- d. Verify your settings and click **Import (X) Virtual Machines** (notice the number in parenthesis is dynamic, depending on the amount of VMs selected).
- e. Verify all *Import Statuses* report back with **OK** and then click on the **Dismiss** button.
- f. Verify that your virtual machines show up in the inventory.



Admin > VM > Inventory > Import Virtual Machines

Please identify the operating system, role, runtime host or host group for each VM. To assign a VM to a host group, the VM must reside on a shared datastore (SAN).

Configure VMs

Virtual Machine Name	Operating System	Role	Runtime Host/Group	Comments
Cisco_Packet_Tracer_Master.PodRouter	Linux	Master	Host 172.16.16.11	
Cisco_Packet_Tracer_Master.Workbench	Linux	Master	Host 172.16.16.11	

Show entries Showing 1 to 2 of 2 items

Import (2) Virtual Machines

For additional information, please refer to the [NETLAB+ VE Administrator Guide](#).

4.3 Building the Master Pod

This section will assist you in adding the *Cisco Packet Tracer Pod* to your *NETLAB+* system.

4.3.1 Enabling Lab Content in Course Manager

Please refer to the *Course Manager* section of the [NETLAB+ VE Administrator Guide](#) on how to enable content. Please install the **Cisco Packet Tracer Pod** course.

4.3.2 Create the Master Pod


1. Log into **NETLAB+ VE** with the *administrator* account.
2. Select the **Pods** icon.




3. Create a new pod by scrolling to the bottom and clicking the **Create New Pod** button.




4. Then, click on the **Cisco_Packet_Tracer** pod design from the list of installed pod types.



5. On the *New Pod* window, input a value into the **Pod ID** and **Pod Name** fields. Click **Next**.



New Pod

Pod Type:  Cisco Packet Tracer VM

Pod ID:

Pod Name:

Used Pod IDs:

10
11
12
13
14
15
16



The **Pod ID** determines the order in which the pods will appear in the scheduler. It is best practice to use a block of sequential ID numbers for the *Pod Id* that allows for the number of pods you are going to install.

The **Pod Name** identifies the pod and is unique per pod.


- To finalize the wizard, click **OK**.

For additional information, please refer to the [NETLAB+ VE Administrator Guide](#).


4.3.3 Attach Virtual Machines to the Master Pod

Update the master pod to associate the virtual machines with the newly created pod.


- Select the **Cisco Packet Tracer Pod** master pod from the pod list.




- Click on the **Action** dropdown next to the virtual machine you are about to assign and select **Attach VM**.



Admin > Pods > Cisco_Packet_Tracer - Master (Pod) > View


Pod ID	Pod Name	Type	Activity	ACL State	State
500	Cisco_Packet_Tracer - Master	 Cisco Packet Tracer VM	IDLE	DISABLED	OFFLINE

Remote PC ²

PC Name	VM	Operating System	VM Role	Runtime Host	Action
PodRouter	ABSENT				
Workbench	ABSENT				

- View
- Settings
- Attach VM**
- Remove VM From...
- Snapshots

3. Select the corresponding virtual machine from the inventory list.



Virtual Machine Name	Operating System	Role	Datacenter	Runtime Host/Group
Cisco_Packet_Tracer_Master.PodRouter	Linux	Master	Netlab	172.16.10.1/1
Cisco_Packet_Tracer_Master.Workbench	Linux	Master	Netlab	172.16.10.1/1

4. Click **OK** to confirm the VM attachment and repeat the previous steps for the remaining virtual machines.


4.3.4 Create Snapshots for the Master Virtual Machines

In order to proceed with pod cloning, snapshots must be created on each of the pod's virtual machines.



Verify that all VMs are still powered off before taking snapshots.

1. Make sure to view the **Cisco Packet Tracer Pod** master pod you just assigned machines to. In the pod view, click on the dropdown menu option underneath the *Action* column for a specific VM and select **Snapshots**.



Admin > Pods > Cisco_Packet_Tracer - Master (Pod) > View


Pod ID	Pod Name	Type	Activity	ACL State	State
500	Cisco_Packet_Tracer - Master	Cisco Packet Tracer VM	IDLE	DISABLED	OFFLINE

Remote PC 2

PC Name	VM	Operating System	VM Role	Runtime Host	Action
PodRouter	Cisco_Packet_Tracer_Master.PodRouter	Linux	MASTER		View Settings Attach VM Remove VM From... Snapshots
Workbench	Cisco_Packet_Tracer_Master.Workbench	Linux	MASTER		

Dismiss Pod Settings Clone Pod View Reservations Configure Pod ACL

2. In the *Snapshot Manager* window, click on the **Take** button. This will take a snapshot of the current state of the virtual machine.



Snapshot Manager

Cisco_Packet_Tracer_Master.PodRoute
You Are Here!

Name:
Description:


Take Delete All Go To Edit Delete

Dismiss




Any changes made after this will require a new snapshot or those changes will not reflect in the reset state of the pod or its clones.

3. In the *Take Snapshot* window, type `Golden_Master` into the *Name* text field, or you may choose another naming convention as long as it is consistent for easy management. Click **OK**.



It is recommended to use `GOLDEN_MASTER` as the snapshot name when working with normalized pod types.

4. In the *Snapshot Manager* window, notice the snapshot is created. Click the **Dismiss** button.




At this point, it is good to verify that you have only one snapshot on the virtual machine. Multiple snapshots increase the likelihood of having problems, especially if the snapshots are named the same. Also, the more snapshots a virtual machine has, the slower the performance and the more drive space is used.

5. Repeat the previous steps for the remaining virtual machines.

4.3.5 Set the Revert to Snapshot

1. In the pod view, click on the dropdown menu option underneath the *Action* column and select **Settings**.




The screenshot shows the NDG interface for a pod named 'Cisco_Packet_Tracer - Master (Pod)'. The pod ID is 500 and its state is OFFLINE. Below the pod information, there is a table of Remote PCs:

PC Name	VM	Operating System	VM Role	Runtime Host	Action
PodRouter	Cisco_Packet_Tracer_Master.PodRouter	Linux	MASTER		View, Settings, Attach VM, Remove VM From..., Snapshots
Workbench	Cisco_Packet_Tracer_Master.Workbench	Linux	MASTER		View, Settings, Attach VM, Remove VM From..., Snapshots

The 'Settings' option in the Action dropdown menu for the PodRouter VM is highlighted with a red box.

2. In the virtual machine's *Settings* window, click on the *Revert to Snapshot* dropdown and select **GOLDEN_MASTER** and then click the **Submit** button.




The screenshot shows the 'PodRouter Settings' window. The 'Revert to Snapshot' dropdown menu is set to 'Golden_Master', which is highlighted with a red box. At the bottom of the window, the 'Submit' button is also highlighted with a red box.

3. On the *Remote PC Updated* window, click **OK** to confirm.
4. Return to the pod view page and repeat the previous steps for the remaining virtual machines.

4.3.6 Bring the Master Pod Online

In the pod view, click the drop-arrow under *State* and select **Bring Pod Online**.



4.4 Testing the Master Pod (optional)

The Cisco Packet Tracer Pod master pod should be tested prior to cloning to ensure that the pod spins up correctly, the networking options function as planned, and the pod reverts back to its snapshot after the reservation is ended. This process consists of:

- Scheduling the master pod
- Testing out the master pod
- Ending the reservation

4.4.1 Virtual Machine Credentials

For your reference, the following table provides a list of the credentials for the systems in the pod:

Machine	User name	Password
Workbench	sysadmin	Train1ng\$

4.4.2 Create Class and Schedule the Master Pod

Create a class as identified in the *Add Classes* section of the [NETLAB+ VE Instructor Guide](#), followed by adding the appropriate content to the selected class, and then schedule the *Master Pod*.



When scheduling the *Master Pod*, it is important to schedule the pod for enough time to complete the following steps. Failure to complete the steps prior to taking the final snapshot could mean redeploying necessary virtual machines.

4.4.3 Test the Master Pod


1. Log in to NETLAB+ using an instructor or student account that has been assigned to the class that was created in the previous step.
2. Launch the **Workbench** virtual machine.
3. After the **Workbench** virtual machine starts up, it should automatically startup Packet Tracer, which requires logging into the Cisco Networking Academy.
 - a. If the Cisco Networking Academy login page does not come up, the most likely cause is that **Network Adapter #1** on the **PodRouter** VM is not connected to a vSwitch Port Group where there is DHCP server and/or Internet access.
4. Log in to the Cisco Networking Academy.
5. Minimize the Cisco Packet Tracer window.
6. Open **Firefox** (which should bring up the Cisco Networking Academy page) and login to the Cisco Networking Academy
7. Load a course that has Packet Tracer labs (i.e., CCNA1/Introduction to Networks v7.0)
8. Go to the Modules section and open the course content into a new window.
9. Navigate to a module that has a Packet Tracer assignment
10. Open the Packet Tracer Assignment (using Packet Tracer).
11. Close the Cisco Networking Academy course
12. Logout of the Cisco Networking Academy site

4.4.4 End Reservation

You may now end the reservation of the master pod.

4.4.5 Take the Master Pod Offline

In the pod view, click the drop-arrow under *State* and select **Take Pod Offline**.



The screenshot shows the NDG interface for managing pods. The breadcrumb trail is: Admin > Pods > Cisco_Packet_Tracer - Master (Pod) > View. Below this is a table with columns: Pod ID, Pod Name, Type, Activity, ACL State, and State. The pod ID is 500, the name is Cisco_Packet_Tracer - Master, the type is Cisco Packet Tracer VM, the activity is IDLE, and the ACL state is DISABLED. The state is ONLINE, and a dropdown menu is open showing the 'Take Pod Offline' option highlighted with a red box. There is also a 'Remote PC 2' button below the table.

Pod ID	Pod Name	Type	Activity	ACL State	State
500	Cisco_Packet_Tracer - Master	Cisco Packet Tracer VM	IDLE	DISABLED	ONLINE

5 Pod Cloning

This section will help you create multiple student pods. The following sections describe the *NETLAB+* pod cloning feature used to create student pods on one or two host systems.

5.1 Linked Clones and Full Clones

NETLAB+ can create *linked clones* or *full clones*.

A **linked clone** (or linked virtual machine) is a virtual machine that shares virtual disks with the parent (or master) virtual machine in an ongoing manner. This conserves disk space and allows multiple virtual machines to use the same software installation. Linked clones can be created very quickly because most of the disk is shared with the parent VM.

A **full clone** is an independent copy of a virtual machine that shares nothing with the parent virtual machine after the cloning operation. The ongoing operation of a full clone is entirely separate from the parent virtual machine.


5.2 Creating User Pods

The following section describes how to create user pods on the same *VMware Host* system that holds your master pod's virtual machines. In this scenario, we will create linked virtual machines using the *NETLAB+* pod cloning utility.


1. Log in to **NETLAB+ VE** with the *administrator* account.
2. Select the **Pods** icon.



3. Click on your master pod.
4. Make sure the pod is offline by selecting **Take Pod Offline**.
5. Click the **Clone Pod** button to create a new pod-based on the settings and snapshots of this pod.



6. Input a new ID value into the **New Pod ID** field. It is advised to keep the pods in numerical order. If the pod IDs are not in numerical order, they will not show up in the scheduler in numerical order. Click **Next**.
7. Enter a name for the cloned pod into the **New Pod Name** field. For example, **Cisco_Packet_Tracer – Pod 501**. Click **Next**.




The **Pod Name** identifies the pod and is unique per pod.

8. When the action has finished processing, you are presented with a settings screen. Notice each VM has its own tab. Go through each tab and verify the following:


Source Virtual Machine:

- a. *From Snapshot* should be set to the **GOLDEN_MASTER** snapshot you created previously.

Target Virtual Machine:


- a. For *Type*, verify that **Linked** is selected.
- b. For *Role*, verify that the **Normal** role is selected.
- c. For *Take Snapshot*, verify that **GOLDEN_MASTER** is inputted.

- When you are done changing settings, click **Clone Pod**. This should complete within a minute as we are creating linked virtual machines.



Admin > Pods > Cisco_Packet_Tracer - Master (Pod) > Clone Pod > Configure Virtual Machine Settings

Clone Pod

Source Pod ID	Source Pod Name	New Pod Type	New Pod ID	New Pod Name
500	Cisco_Packet_Tracer - Master	 Cisco Packet Tracer VM	501	Cisco_Packet_Tracer - Pod 501

Click on the tabs below to configure virtual machine settings for each remote PC in the pod.



PodRouter | Workbench

Source Virtual Machine → Target Virtual Machine

Source Virtual Machine	Target Virtual Machine
VM Name: Cisco_Packet_Tracer_Master.Po...	VM Name: Cisco_Packet_Tracer - Pod 501 PodRo
From Snapshot: Golden_Master	Type: Linked
	Role: Normal
	Runtime Host: [Redacted]
	Datastore: [Redacted]
	Storage: On Demand
	Take Snapshot: Golden_Master

Previous | **Clone Pod** | Cancel

- When the pod clone process is finished, click **OK**.
- If you want to dedicate this pod to a particular class, team, or student, use the *Pod ACLs* feature. For details, see the [NETLAB+ VE Instructor Guide](#).
- Click the **Online** Button on the *Pod Management* page to make the pod available.

Activity	ACL State	State
IDLE	 DISABLED	 OFFLINE

Bring Pod Online

The user pod can now be reserved. When the reservation becomes active, *NETLAB+* will automatically configure virtual machines and virtual networking for your new pod.



The *GOLDEN_MASTER* snapshot is the starting point for all pods. We recommend that you reserve the 1st pod and conduct some labs to make sure the snapshot images work correctly. If there are defects, make corrections to the images to the master pod and retake the *GOLDEN_MASTER* snapshot before creating additional pods.


5.3 Copying Your Master Pod to the Second Host

For this task, we will use the pod cloning utility to copy our master pod to the second host.

1. Log in to *NETLAB+* with the administrator account.
2. Select the **Pods** icon.



3. Click on the master pod.
4. Make sure the pod is offline by selecting **Take Pod Offline**.
5. Click the **Clone** button to create a new pod-based on the settings of this pod.



6. Input a new ID value into the **New Pod ID** field. It is advised to keep the pods in numerical order. If the pod IDs are not in numerical order, they will not show up in the scheduler in numerical order. Click **Next**.
7. Enter a name for the cloned pod into the **New Pod Name** field. For example, **Cisco_Packet_Tracer – Master.Host2**. Click **Next**.



The **Pod Name** identifies the pod and is unique per pod. If you will be creating master pods on multiple hosts, it is recommended that you name each master pod with an identifier as to which host. For example, on the first host, the master pod might be called:

Cisco_Packet_Tracer – Master.Host1

And on the second host, the master pod might be called:

Cisco_Packet_Tracer – Master.Host2


- When the action has finished processing, you are presented with a settings screen. Notice each VM has its own tab. Go through each tab and verify the following:

Source Virtual Machine:

- From Snapshot* should be set to the **GOLDEN_MASTER** snapshot you created previously.

Target Virtual Machine:

- For *Type*, verify that **Full** is selected.
 - For *Role*, verify that the **Master** role is selected.
 - For *Take Snapshot*, verify that **GOLDEN_MASTER** is inputted.
 - For *Runtime Host*, select the second host system (which should be different than the system you are cloning from).
- When you are done changing settings, click **Clone Pod**. This may take up to 30 minutes as full copies are being made. You may navigate away from the cloning progress screen, and then later return to the pod to check progress.



- When the pod clone process is finished, click **OK**.
- It is likely that you will need to reactivate the licensing on any Windows VMs in the Master pod on the second (third, etc.) host. Please test the master pod prior to cloning student pods.

5.4 Creating User Pods on the Second Host

To create user pods on the second host, repeat the steps to create user pods on the first host (see [Creating User Pods](#)), substituting the second master pod (created in the previous section) as the cloning source.

5.5 Assigning Pods to Students, Teams, or Classes

Please refer to the [NETLAB+ VE Instructor Guide](#) for details on using the *Pod ACLs* feature.